

تسلسل ITEM	الرقم الرمزي VOCABULARY NO.	المواصفات DESCRIPTION	الوحدة UNIT	الكمية QUANTITY	المبلغ VALUE	X O R D	الملاحظات
		<u>MULTI PURPOSE SUPER DUTY FIRE TRUCK</u>					
		1. <u>CHASSIS</u> :- MAKE / KENWORTH , OSHCOSH , MAC , STERLING , RPI 52.1250. (ROSENBAUER) GVWR / 42 - UP TO 50 TON DRIVE / (8 x 8) OR (8 x 4) (KESSLER) REAR AXLE LOAD = (2 x 16) TON MIN TYRES = 9 x (445 x 80 R25) TRANSMISSION = FULLY AUTOMATIC WITH RETARDER ENGINE / CATERPILLAR EURO 4. OR MB – OM / CUMMENCE BRAKE = DUAL CIRCUIT, DISC TYPE COMPLYING WITH ECE R13 STEERING ; (ZF) POWER STEERING ELECTRIC SYS. 24 VOLT TOP SPEED = ABOUT 120 KM/HR CAB. = CREW CAB (5 + 1) WITH PUBLIC ADDRESS SYS. & A/C SYSTEM FOR TROPICAL AREA COMPLY WITH ECE R 29	NOS	2			
		2. <u>PURPOSE</u> - WATER / FOAM & DCP COMPATING UNIT - AIRIAL EXTENDED ARM MONITOR FOR ELEVATED THREW. INCLUDE (IR) CAMERA 3. <u>CAPACITIES</u> WATER / (16 – 18)M3 FOAM CONCENTRATE / (2500) LIT DCP / (500) KG 4. <u>PUMPS</u> A. WATER UP TO 10000 (LPM) @ 10 BAR (REAR MOUNTED) ALUM . BODY WITH S.STEEL SHAFT & IMPELLERS B. FOAM SYSTEM ROSENBAUR (FOAMATIC RVME 600) OR EQUIVALENT INCLUDE BALANCED PRESSURE FOAM ADMIXING SYSTEM C. PRIMING UNIT = ELECTRICAL TYPE					

		5. <u>TANKS</u> -TO BE S.STEEL AISI 316 L SEMI - RECTANGULAR (WITH NO RIGHT ANGLES) RENFORCED BY INSIDE BUFLERS; TORSION FREE ABILITY MULTIBLE SHOCK COMPENSATOR, WITH STD. ACCESSORIES & INSTRUMENTS 6. <u>REAR CONTROL PANEL</u> INSIDE PUMP PAY ENCLOSUSR & CAB CONTROL COMPRISES ALL FUNCTION AND ACCESS REQUIRED WITH (BACK – UP) FACILITIES PNEUMATICALLY OPERATING FOR ALL PUMPING SYS. AND TURRENT MONITOR 7. <u>EXTENDED ARIAL ARM MONITOR (6000 – 7000) LPM</u> TO BE TELESCOPIC; ARTICULATED EASY TO DEPLOY WITH QUICK RIGGER SYSTEM INCLUDE (FAIL SAFE) REQUIRMENTS FITTED WITH (IR) CAMERA			
		8. <u>DELIVERIES & INTAKES</u> - (3 x 2.5) BSS (336) FEM FOAM / WATER – DELIVERIES EACH SIDE (REAR) - (2 x 4 “) BSRT. FEM. DISCHARGE DELIVERIES FOR MASSIVE FLOW ONE EACH SIDE - (2 x 2.5 “) BSS (336) MALE W / NRV - FOR PRESS - INTAKE - (2 x 5 ") BSRT MALE (REAR) MOUNTED OR ONE EACH SIDE SUCTION PORTS .WITH BLANK CUP 9. <u>HOSE REELS</u> - W/ FOAM TYPE (2 x 30 x 1.25" x DIA) MANUAL / REWIND & ELECTRICAL WITH NON – COLAPSIBLE FLEXIBLE HOSE - ONE POWDER HOSE REEL (1.25" x 25 MTR) WITH FLUSHING FUNCTION 10. <u>BODY WORK & SUPER STRUCTURE</u> - TOP ROOF ALUM . PLATING WITH HAND RAIL - PUMP PAY – ALUM. STRUCTUR & ALUM. CALDING WITH LED DOOR - TOOLS COMPARTMENTS ONE EACH SIDE WITH ROLLER SHUTTERS			

		11. <u>ACCESSORIES</u> - (10 x 2.5 “) PRESSURE HOSE WITH COUPLINGS (PVC) LINING - 4 x FOAM B.PIPE (400 – 500 LPM) LIGHT ALLOY - 4 x WATER NOZZEL VARIABLE FLOW / SPRAY / JET BATTERN (TURBO TYPE) - (5 x 15 MTR x 4”) BSRT COUPLING PRESSURE HOSE (FLEXIBLE) - 2 x DIVIDING HEAD (4” x 2 x 2.5 “) ALUM. (BSS-STANDER) - 5" x SUCTION HOSES 5 “ BSRT COUPL (3 MTR LENGTH) - 10 x SUCTION SPANNERS - 2 x FIRE EXTINGUSHER - 2 x ADAPTER (5" x 4" BSRT(FEM x MALE)) - 2 x FORCED DISMANTELING TOOL - 1 x LIGHTING MAST (PORTABLE) TRIO - 5 x (SCPA) – SCOTT TYPE					
--	--	---	--	--	--	--	--