

MISSAN OIL COMPANY

REQUISITIONS LIST

CLOSING DATE 5/11/2012

ALL PARTICIPANTS IN ENQUIRIES THAT WILL BE RE- ANNOUNCED SHOULD FOLLOW -UP OUR REQUISITIONS LISTS AND CLOSING DATE ON OUR WEB SITE INSTEAD OF NOTIFICATION BY FAX OR E-MAIL AND SUBMIT EITHER RENEWED OFFERS OR LETTERS BY WHICH EXTENDING THE VALIDITY OF THEIR PAYMENT FOR PARTICIPATION SHOULD BE DONE ONE DAY BEFORE CLOSING DATE . SINCE CLOSING DATE IS DEDICATED FOR RECEIVING OFFER (S) ONLY FOR TECHNICAL SPECIFICATION PLEASE VISIT OUR WEB SITE (www.moc.oil.gov.iq) OTHERWISE, FEEL FREE TO CONTACT US AT (moc_cd@moc.oil.gov.iq)

ANN-NO. -48-

SER	ENQ.REF.	SPEC	NO. OF ITEMS	NOTE	MAT NAT
1	74.11.4112	WELL HEAD AUTOMATIC SAFETY VALVE	1		Re-ann
2	11.12.4139	Oil spill response trailer	1		
3	58.12.4140	Breather valve for fixed roof oil flow tank	2		
4	58.12.4141	PRESSURE GAUGES	6		

74.11.4112

WELL HEAD AUTOMATIC SAFETY VALVE

<i>QTY</i>	<i>UNIT</i>	<i>DES</i>	<i>ITEM</i>
40	NOS.	3" x 5000 PER API 6A 17th EDITION SPECIFICATION FULL BORE METAL/METAL SEATING , RISING STEM , FLANGED EACH SIDE . NORMINAL FLANGE SIZE : 3" , MINIMUM BORE SIZE : 3 1/8" API RING GASKET R35 WITH SELF REVERSE ACTING ACTUATOR , VISUAL INDICATOR , OPEN CLOSE POSITION . ACTUATOR SHOULD INCLUDE HIGH AND LOW PILOT BLOCK SETTING PRESSURE SHOULD BE (HIGH : 35 KG/CM² - LOW : 7 KG/M²) WITH MANUAL OVERRIDE ON LOW PILOT FOR VALVE REOPENING SET OF HIGH PRESSURE TUBE + FITTINGS FOR PRESSURE CONNECTION FROM PRESSURE IN TAKE TO ACTUATOR PILOTS + NEEDLE VALVE + VELOCITY CHECK VALVE + MANUAL REOPENING DEVICE , QUOTED AS PER API 6A 17th EDITION PSL2 MATERIAL CLASS DD , TEMP. CLASS U .	1

Recommended

1. Supply of all mill tests certificates for individual items including all tests (performed , heat analysis, chemical composition, mechanical and hydrostatic tests) . These certificates should be issued by third party who is performing inspection activities at the mill,
Such third party should be a well-known inspection company and accepted by MOC such as DNV , LLOYDS , INTERTEK , BUREAU VERITAS .
2. The supplier should present complete set of printed documents .
3. Vender list should be submitted within offer for each item Cleary stated the manufactures and country of origin of materials .
4. Origin and manufacturer of main parts should fixed on clear place as punched letters .
5. Point of entry should be stated as CIP Missan .
6. Commercial offer should be in (US. Dollar) only .
7. Relevant catalogues, diagrams and data sheet to be submitted within the technical offer.
8. Origin of material should be from Cameron Co. , Breda Co. , OTIS Co. and manufactured at
(USA , CANADA , UK , FRANCE , ITALY , GERMANY , SINGAPORE) .
9. Origin certificate should be submitted approved by commerce & industry chamber , authinticated by Iraqi counsulate .

		ITEM
المواصفات الفنية	80 %	1
المنشأ	10 %	2
المدة المتعلقة بتنفيذ العقد	5 %	3
الأعمال المنجزة ضمن الاختصاص	5 %	4