

Financial Offer: Purchasing Items & Implement the project of the Center of Tamayouz Studio

العرض المالي: شراء مواد وتنفيذ مشروع مركز ستوديو التميز

#	Item Description	Unit	QTY	Unit Price (USD)	Total Price (USD)
A) Mixers					
1	4 input global production streaming/recording switcher	PCS	1		
	8 x Primary, 1 x Title Input Switcher NTSC/PAL, HD Input Supported Individual Frame Synchronizer per Input Internal 1080i Processing Hardware Buttons and LCD Touchscreen Cut, Mix, Wipe, and Keyer Effects Built-In Live Streaming Encoder Record Program to SD Card Slot in AVCHD Built-In Audio Mixer Mac, PC, and Tablet Integration				
2	Multi-channel audio recorder	PCS	1		
	8+2 and 12+2 channel frame sizes Built-in 24 bit Lexicon digital effects processor 32 FX settings Tap Tempo and FX setting store function 1 FX send on each channel 1 configurable auxiliary bus XLR-type and ¼" metal jack connector sockets RCA phono stereo playback inputs and record outputs 3-band EQ with a swept mid on mono inputs 3-band EQ on stereo inputs TRS insert sockets and inserts on all mono inputs Ten-segment LED output metering Intuitive and comprehensive solo system Headphone output Easily rack mountable Custom Karaoke preset				
Total Amount (US Dollars) Table (A)					
B) Camera and Accessories					
1	Camcorder with dual pixel autofocus	PCS	4		
	8.29MP, 1" CMOS Sensor Up to UHD 4K30 Video Recording Mini-HDMI and 3G-SDI Outputs Integrated 15x Optical Zoom Lens Dual XLR and Mic/Line Audio Input 5-Axis Optical Image Stabilization Dual-Pixel CMOS Autofocus Feature Dual SD Relay and Simultaneous Recording DIG!C DV 6 Processor 3" Touchscreen LCD, Tilttable Viewfinder				
2	4K SDXC UHS-II Memory Card	PCS	8		
	128GB Storage Capacity UHS-II / V60 / U3 / Class 10 Sustained Read Speed: 260 MB/s Sustained Write Speed: 140 MB/s Minimum Write Speed: 60 MB/s Records Full HD, 3D, and 4K Video Shock / Dust / Water / Temperature Proof X-Ray & Magnetic Proof Built-In Write Protect Switch Supports Advanced Shooting Modes				
3	Starter Series 19 Teleprompter & software	PCS	1		
	Complete 17" Entry-Level Teleprompter Use w/ DSLR to Standard Size ENG Cameras 300 Nit Brightness; 1000:1 Contrast 70:30 Broadcast Quality Prompter Glass Reading Range - up to 20' (6m) Teleprompter Hood Ready-Built Mounting System for Tripods Dual-Screen Functionality Offers Multi-Language Text & Menus Software (Mac/Win) & USB Security Dongle				
4	Carbon fiber video Tripod kit with BVX16H head for Autocue	PCS	1		
	Heavy-Duty Tripod, Mid-Level Spreader 35-lb System Capacity 100mm Half-Ball Fluid Head Plate with 2-Screw Mounting Soft Carrying Bag				

#	Item Description	Unit	QTY	Unit Price (USD)	Total Price (USD)
5	Dual-stage video tripod kit	PCS	3		
6	Battery charger	PCS	1		
7	Battery pack	PCS	1		
8	Digital Camera	PCS	1		
9	Camera Tripod	PCS	1		

Total Amount (US Dollars) Table (B)

C) Audio

1	Wireless monitor set (4Pcs)	PCS	1		
2	Handheld Lavalier set	PCS	3		
3	Studio headphones	PCS	5		
4	Desktop gooseneck condenser microphone	PCS	1		

#	Item Description	Unit	QTY	Unit Price (USD)	Total Price (USD)
5	Thunderbolt and USB Portable Audio Interface USB & Thunderbolt Interface 32-Channel AD/DA at 24-Bit/192 kHz 4 Mic/Line Inputs and 4 Line/Hi-Z Inputs Touchscreen Display	USB & Thunderbolt Interface 32-Channel AD/DA at 24-Bit/192 kHz 4 Mic/Line Inputs and 4 Line/Hi-Z Inputs Touchscreen Display 2 Headphone Outputs and 2 ReAmp Outputs Supports USB, ADAT, S/PDIF & Thunderbolt Included Hardware Emulations Included Digital Control Panel Remote Control via Smartphones & Tablets Portable Tabletop Construction	PCS	1	
6	Dynamic Broadcast Microphone Dynamic directional characteristic Mint condition shows almost no sign of use He Neumann b CM 705 is a professional microphone with dynamic capsule that gives you great quality so	For Broadcast Studios and Individuals Dynamic Microphone Capsule Designed for Speech Reproduction Removable Head Grille for Quick Cleaning Integrated Pop Screen Hypercardioid Directional Polar Pattern Compatible with Standard Studio Booms No Power Supply Required	PCS	1	
7	Powered Studio Monitor with 5.25" Kevlar Woofer 5.25" Kevlar Woofer 1" Silk Dome Tweeter 40W LF, 30W HF Output Power 60 to 22,000 Hz Frequency Response	5.25" Kevlar Woofer 1" Silk Dome Tweeter 40W LF, 30W HF Output Power 60 to 22,000 Hz Frequency Response Rear Panel Volume Control Magnetically Shielded Enclosure RF Interference Protection Circuit Output Protection Circuit Heat Protection Circuit	PCS	2	
Total Amount (US Dollars) Table (C)					
D) Cables and Studio Equipment					
1	HD cable	Center conductor: 18 AWG stranded Double Braided Shield Outer Diameter: 7.2mm Max transmission distance: 3G-SDI 60m, HD-SDI 87m Insulation: Highly-Foamed PE Jacket: PVC Dielectric strength: 1000V AC/min.	PCS	1	
2	Audio cable	2-Conductor Cable Braided Copper Shield Rejects EMI & RFI	PCS	1	
3	HD connector with cover	3.0 GHz 75-Ohm BNC Plug for L-4.5CHWS/1694F Cables	PCS	1	
4	Audio connector	3-Pole Male XLR Connector 3-Pole Female XLR Connector	PCS	1	
5	Adapter jack	Converts from 1/4" to 1/8" Mini Plug 5.9" Length Gold-Plated Contacts	PCS	1	
6	Audio Connector	Ø 6,3 mm stereo plug 2 x Ø 6,3 mm stereo socket	PCS	1	
7	Ceiling stand	Height: from 860 to 1,560 mm Height adjustment: clutch Material: steel Mounting: attaches to ceilings Rod combination: 2-piece folding design Threaded connector: 3/8" Type: black Weight: 1.34 kg	PCS	1	
8	Mic Table Stand	Mic Table Stand	PCS	2	
9	Desktop computer with high specs	I9 9900 Ram 32gb adata Mb z390 Msi carbon ac Vga 2080 super Hdd 1 tb Ssd m.2 512 Case Thermaltake Psu 750w	PCS	1	

#	Item Description	Unit	QTY	Unit Price (USD)	Total Price (USD)
10	Desktop computer	PCS	1		
	1 x Intel Xeon E-2144G Quad-core (4 Core) 3.60 GHz - 16 GB DDR4 SDRAM - NVIDIA Quadro P2000 5 GB Graphics - Windows 10 Pro 64-bit (English) - Small Form Factor Tower Black 3FQ51UT#ABA				
11	Display Monitor with Fully Adjustable Dual Monitor	PCS	1		
	Monitor Stand: Dual monitor stand with heavy duty desk clamp for mounting on the back of desks, detachable VESA bracket plates, and fully adjustable arms Display Quantity: 2 Interfaces Supported: 1 x HDMI, 1 x DisplayPort, 1 x DVI-D, 2 x USB 3.1 Type-C, 3 x USB 3.0 Standard Contrast Ratio: 1000:1 Dynamic Contrast Ratio: 1000000:1 Maximum Resolution Supported: 2560 x 1440 Response Time: 5 ms Screen Mode: QHD Brightness: 350 Nit Input Power: 100 - 240 VAC Dimensions: (W x D x H): 24.1 x 1.85 x 14.33 inch Display Features: Swivel, Tilt, Vesa Mount Compatible, Anti-glare, In plane switching, Language selection, LED Backlights, On-screen controls, Pivot rotation, Plug and Play, User programmable, Low Haze, Energy Star Certified Included Accessories: Dual Monitor Desktop Mount Monitor Stand with Heavy Duty Adjustable Clamp				
Total Amount (US Dollars) Table (D)					
E) Lighting systems					
1	LED Light Kit with V-Mount Battery Plate Beam Angle: 105° Color Temperature: 2700-6500K CRI: 96, TLCI: 96, CQS: 95 DMX, Bluetooth, 2.4 GHz Wireless Remote	PCS	2		
	Beam Angle: 105° Color Temperature: 2700-6500K CRI: 96, TLCI: 96, CQS: 95 DMX, Bluetooth, 2.4 GHz Wireless Remote 0-100% Dimming, Flicker Free Bowens-S Type Reflector Mount Multi-Voltage AC, Optional Battery Power				
2	LED Light Kit with V-Mount Battery Plate 5500K Daylight Color Temperature CRI/TLCI: 96/97 18 dB Quiet Fan, Onboard DMX Wired Controller Box	PCS	2		
	5500K Daylight Color Temperature CRI/TLCI: 96/97 18 dB Quiet Fan, Onboard DMX Wired Controller Box Wireless Remote with 328' Range V-Mount Battery Plate Built-In Handle Includes Dedicated Carrying Bag				
3	Grid, and Gel Holder for LS 120d/II and LS 300d/II LED Lights	PCS	2		
	4-Way Barndoors Magnetic Gel Holder 30-Degree Honeycomb Grid				
4	Attachment 6" Lens Diameter Dual Lens Design Boosts Output Beam Spread Variable from 12 to 40° Exclusively for LS C120d, C120dII, C300d	PCS	2		
	6" Lens Diameter Dual Lens Design Boosts Output Beam Spread Variable from 12 to 40° Exclusively for LS C120d, C120dII, C300d C120d II is Up to 14x Brighter with Lens				
5	Softbox	PCS	2		
	26" Diameter, Bowens Mount Absorbs 1 Stop, 270° Beam Spread Comes w/ Skirts to Control Light Radius Use on LED or Strobe Lights Sets up in Seconds, Includes Carry Case				
6	LED Light with Wireless Controller Box and Sony V-Mount Battery Plate Variable Color Temperature: 3200-5500K 1536 Individual LEDs Beam Angle: 45°, CRI: 95	PCS	2		
	Variable Color Temperature: 3200-5500K 1536 Individual LEDs Beam Angle: 45° CRI: 95 Supports AC or Battery Power Wireless Controller Box Remote Dimming/Color Tuning, DMX Control Aluminum Alloy Housing, Manual Yoke Four-Way Barndoors and Diffusing Paper				
7	3X6m Chrome	PCS	1		
	3X6m Chrome				
Total Amount (US Dollars) Table (E)					

#	Item Description	Unit	QTY	Unit Price (USD)	Total Price (USD)
F) Implementation and Studio Room Adaptation					
1	Installing, Operating And Training on Herewith Mentioned Units	LS	LS		
2	Studio Floor, Including sound isolated On The Station	M ²	20		
3	Good Quality studio Chair	PCS	4		
4	Good Quality Table	PCS	1		
5	sound isolated Wall adapitation 60m	M ²	60		
6	sound isolated Ceiling Covering 4m*5m=20m ²	M ²	20		
7	Glass Partition between the media monitoring room and media recording room 3m*5m =15M ²	M ²	15		
8	sound isolated Studio Door 2m *1m	PCS	2		
9	2mX3m Flex (background logo)	PCS	4		
10	truss holders for lighting equipment of all shapes	M ²	25		
Total Amount (US Dollars) Table (F)					
Grand Total Amount (US Dollars) Table (A+B+C+D+E+F)					

NOTE:

1. Our organization is not bound to buy the whole quantity mentioned in the Financial Offer.
2. Our organization is not bound to contract with one company and can split the award between one or more companies.
3. The items must delivered to project site - IRAQ as per the instruction of Our Organization's Supervisor .
4. The offered Price includes, transportation, loading & unloading and any other cost to deliver to the project site.

ملاحظة:

1. منظمنا ليست ملزمة بشراء الكمية الكاملة المذكورة في جدول الكميات.
2. المنظمة ليست ملزمة بان تتعاقد مع شركة واحدة، ويمكن تجزئة العطاء بين أكثر من شركة.
3. يتم التسليم للكميات المذكورة اعلاه في موقع العمل - العراق وحسب خطة المقدمة من قبل مشرف المشروع للمنظمة .
4. الأسعار المقدمة جميع المصاريف من نقل و تحميل و التسليم في الموقع المذكور .

Name of Signatory:.....

Title of Signatory:.....

Name of Bidder:.....

Signature & stamp:

Date of Signing:.....