

B-BSP-11

#	items	Unit	quantity	picture of the item	specifications
1	tire change machine	Piece	1		Max Wheel Width: 12.5" lbs Max Tire Diameter: 38" Outside Clamping Range: 6" - 24" Power Unit: 110V /15 Amp /1Ph
2	9.5L Pneumatic / Manual Oil & Fluid Extractor with Brake Bleeder Hose	Piece	1		1. Air inlet: 1/4" 2. Avg. air con.: 2 cfm @ 90 psi (57 L/min @ 6.3 bar) 3. Fluid temperature range: 1°C- 95°C (35°F- 200°F) 4. Working pressure range: 40~170 psi (2.8~11.7 bar ; 0.28~1.17 mpa)
3	0.8 HP 24 Litres Oil Free Copper Air Compressor	Piece	1		Voltage: 220-240V~50Hz Input power: 600W (0.8HP) Tank: 24Litres (6.3Gal) Oil Free system Noise: 60db Copper Wire motor No-load speed: 1440 RPM Operation pressure: Max. 8 Bar
4	water pump motor 3/4 HP	Piece	1		Maximum Feet of head:20M Material type:Cast Iron, steel, Ceramic Carton Maximum Flow Rate:50M^3 Motor power Type:Electric Outlet Connection Size:0.32inchesMaximum Pressure:1.0MPA
5	Wheel Balancing Machine with car wheels, hydraulic floor jack and lug wrench	Piece	1		Rim diameter: 10"-24" Max tire diameter :1000mm Tire width: 1.5"-16" Max tire weight :70kgs Rotation speed: 200r/min Balance precision :1g Motor :220V/250W
6	Tire Puncture Repair Tool Kit	Piece	1		
7	Nitrogen Tyre Inflator	Piece	1		Input pressure:9.5 kgf/cm sq Purity of Nitrogen:95% Tank Size:60 ltrs Output Pressure:8.5kgf/cm sq Nitrogen Generating capacity:3500/ hours Dimension (l x b x h):620x 430x 1260x mm
8	Hydraulic Trolley Floor Jack 2 Ton Heavy Duty for Car Lift	Piece	2		360 degree Swivel Saddle For Solid Load Contact Lightweight For Fast Positioning and Maneuverability Heavy Gauge SteelFrameProvides Strength and Durability Rust Resistant Finish For Long Life